



DECLARATION OF PERFORMANCE

n° 2207042

External doorset Full WOOD

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul


CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor Impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		(d) Mechanically secured in closed position
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1652 at 2202 mm		
Machecoul, 20/07/2017 François Guérin, General Manager			Signature 



DECLARATION OF PERFORMANCE

n° 2 2 0 8 0 4 2

External doorset Glazed WOOD

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		(d) Mechanically secured in closed position
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1652 at 2202 mm		
Machecoul, 20/07/2017			Signature
François Guérin, General Manager			



DECLARATION OF PERFORMANCE

n° 2 2 32 0 4 2

External doorset WOOD

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor Impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmalm_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		(d) Mechanically secured in closed position
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1752 at 2202 mm		
Machecoul, 01/10/2015		Signature	
François Guérin, General Manager			



DECLARATION OF PERFORMANCE

n° 2 2 33 0 5 2

External doorset Full STEEL

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		(d) Mechanically secured in closed position
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes	non applicable		
only (d)			
Height	of 1667 at 2117mm		
Machecoul, 03/07/2015		Signature	
François Guérin, General Manager			



DECLARATION OF PERFORMANCE

n° 2 2 34 0 5 2

External doorset Glazed STEEL

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		(d) Mechanically secured in closed position
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1667 at 2117mm		

Machecoul, 03/07/2015

François Guérin, General Manager

Signature



DECLARATION OF PERFORMANCE

n° 2237012

External doorset Full ALUMINUM

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at :
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			(d) Mechanically secured in closed position
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1658 at 2458mm		

Machecoul, 20/07/2017

François Guérin, General Manager

Signature



DECLARATION OF PERFORMANCE

n° 2 2 38 0 1 2

External doorset Glazed ALUMINUM

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul


CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	.		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An Informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1658 at 2458mm	(d) Mechanically secured in closed position	
Machecoul, 20/07/2017 François Guérin, General Manager			Signature 



DECLARATION OF PERFORMANCE

n° 22 39 0 1 2

External doorset Flush glazed ALUMINUM

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at :
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			(d) Mechanically secured in closed position
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1658 at 2458mm		

Machecoul, 20/07/2017

François Guérin, General Manager

Signature



DECLARATION OF PERFORMANCE

n° 2240022

External doorset Full WOOD

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/danqm/ain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		(d) Mechanically secured in closed position
Load-bearing capacity of safety devices (b)	non applicable		
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1746 at 2196 mm		
Machecoul, 13/09/2016 François Guérin, General Manager		Signature	



DECLARATION OF PERFORMANCE

n° 2 2 4 1 0 2 2

External doorset Glazed WOOD

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at :
- Test pressure	NPD		http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		(d) Mechanically secured in closed position
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes	non applicable		
only (d)			
Height	of 1746 at 2196 mm		
Machecoul, 13/09/2016		Signature	
François Guérin, General Manager			



DECLARATION OF PERFORMANCE

n° 2 2 42 0 4 2

External doorset Flush glazed WOOD

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		(d) Mechanically secured in closed position
Load-bearing capacity of safety devices (b)	non applicable		
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1652 at 2202 mm		
Machecoul, 20/07/2017 François Guérin, General Manager			Signature



DECLARATION OF PERFORMANCE

n° 2 2 46 0 5 2

External doorset Full STEEL

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at :
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		http://ec.europa.eu/enlenterprise/construction/internal/dangsub/dangmair_en.htm
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			(d) Mechanically secured in closed position
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes	non applicable		
only (d)			
Height	of 1634 at 2184mm		

Machecoul, 20/07/2017

François Guérin, General Manager

Signature



DECLARATION OF PERFORMANCE

n° 2 2 4 7 0 5 2

External doorset Glazed STEEL

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	.		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		(d) Mechanically secured in closed position
Load-bearing capacity of safety devices (b)	non applicable		
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1634 at 2184mm		
Machecoul, 20/07/2017		Signature	
François Guérin, General Manager			



DECLARATION OF PERFORMANCE

n° 2248042

External doorset Full WOOD

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	.		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			
- Test pressure	NPD		(c) Indoor impact means influence on the indoor air quality. An Informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at :
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		
Acoustic	NPD		http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		(d) Mechanically secured in closed position
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1746 at 2196 mm		

Machecoul, 20/07/2017

François Guérin, General Manager

Signature



DECLARATION OF PERFORMANCE

n° 22 49 052

External doorset Flush glazed STEEL

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor Impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		(d) Mechanically secured in closed position
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	#N/A		
Machecoul, 20/07/2017 François Guérin, General Manager			Signature



DECLARATION OF PERFORMANCE

n° 2 2 5 1 0 5 2

External doorset Flush glazed STEEL

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul


CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		(d) Mechanically secured in closed position
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1634 at 2184mm		
Machecoul, 04/06/2018			Signature 
François Guérin, General Manager			



DECLARATION OF PERFORMANCE

n° 2 2 52 0 5 2

External doorset Flush glazed STEEL

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul


CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmair_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		(d) Mechanically secured in closed position
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1634 at 2184mm		
Machecoul, 11/06/2020 François Guérin, General Manager			Signature 



DECLARATION OF PERFORMANCE

n° 2 2 53 0 5 2

External doorset Flush glazed STEEL

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/danqsub/danqm ain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		(d) Mechanically secured in closed position
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1667 at 2117mm		
Machecoul, 11/06/2020 François Guérin, General Manager		Signature	



DECLARATION OF PERFORMANCE

n° 2 2 55 0 2 2

External doorset Full WOOD

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at :
- Test pressure	NPD		
- Frame deflection	NPD		
Load-bearing capacity of safety devices (b)	non applicable		http://ec.europa.eu/enterprise/construction/internal/danqsub/danqmain_en.htm
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			(d) Mechanically secured in closed position
- Solar factor	NPD		
- Light transmittance	NPD		
Air permability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1746 at 2196 mm		

Machecoul, 19/05/2021

François Guérin, General Manager

Signature



DECLARATION OF PERFORMANCE

n° 22 56 012

External doorset Full ALUMINUM

Communication in domestic and commercial locations

Société Bel'm, 2 rue Gustave Eiffel BP41 - 44270 Machecoul

CSTB (N°0679) and FCBA (N°0380) have realized calculations and type tests following the system 3. He has issued the test reports and corresponding calculations.

NF EN 14351-1 +A2 : 2016

Windows and external pedestrian doorsets

without resistance to fire and/or smoke leakage characteristics.

PERFORMANCES STATED

Essential characteristics	Performances	Harmonized technical specifications	
Watertightness (a)	NPD	NF EN 14351-1 +A2 : 2016	(a) Including durability
Dangerous substances (c)	-		(b) Threshold levels have been identified by the technical specification writers
Resistance of wind load			(c) Indoor impact means influence on the indoor air quality. An informative database of European and national provisions on dangerous substances is available on the EUROPA website of the Construction accessed at : http://ec.europa.eu/enterprise/construction/internal/dangsub/dangmain_en.htm
- Test pressure	NPD		
- Frame deflection	NPD		(d) Mechanically secured in closed position
Load-bearing capacity of safety devices (b)	non applicable		
Acoustic	NPD		
Thermal transmittance	NPD		
Radiation properties			
- Solar factor	NPD		
- Light transmittance	NPD		
Air permeability	NPD		
Ability to release (a)			
locked doors in escape routes only (d)	non applicable		
Height	of 1658 at 2258mm		
Machecoul, 19/05/2021 François Guérin, General Manager			Signature 